

ОДНОФАЗОВЫЙ ТЕПЛООБМЕННИК - Design ТИП ТЕПЛООБМЕННИКА : B25THx50/1P

Рабочая среда, сторона 1 : Water
Рабочая среда, сторона 2 : Water

СТОРОНА 1 : внутренняя цепь
СТОРОНА 2 : внешний контур


Flow Type : Counter-Current
SSP Alias : B25T

ИСХОДНЫЕ ДАННЫЕ		СТОРОНА 1	СТОРОНА 2
Передаваемая мощность	kW	142,1	
Температура на входе	°C	80,00	50,00
Температура на выходе	°C	60,00	70,00
Расход	kg/s	1,695	1,698
Потери напора, заданные	kPa	50,0	50,0
Тепловая длина		2,000	2,000
ТЕХНИЧЕСКИЕ ПАРАМЕТРЫ		СТОРОНА 1	СТОРОНА 2
Поверхность нагрева	m ²	3,02	
Тепловой поток	kW/m ²	47,0	
Логарифм средней разности температур K		10,00	
Кэф. теплопередачи (расч./требуемый) W/m ² ,°C		8210	
Потеря напора*	kPa	52,6	49,3
- в портах	kPa	6,86	6,85
Диаметр порта	mm	24,0	24,0
Number of channels per pass		24	25
Количество пластин		50	
Поправка на загрязнение	%	75	
Кэфф. загрязнения	m ² ,°C/kW	0,089	
Число Рейнольдса		3092	2575
скорость порта	m/s	3,83	3,82
ФИЗИЧЕСКИЕ СВОЙСТВА		СТОРОНА 1	СТОРОНА 2
Реперная температура	°C	70,00	60,00
Вязкость	cP	0,404	0,467
Вязкость на стенках	cP	0,429	0,437
Плотность	kg/m ³	977,7	983,2
Теплоемкость	kJ/kg, °C	4,192	4,185
Теплопроводность	W/m, °C	0,6631	0,6544
Largest wall temperature difference	K		1,45
Средняя температура поверхности стенок	°C	55,87	54,41
Maximum wall temperature	°C	75,87	74,41
Коэффициент теплопередачи пленки	W/m ² , °C	19900	18600
Average wall temperature	°C	65,82	64,53
Скорость потока в канале	m/s	0,320	0,306
Напряжение на сдвиг	Pa	95,6	88,7

TOTALS

Total weight empty	kg	9,92 - 12,8
Total weight filled	kg	15,3 - 18,1
Hold-up volume, inner circuit	dm ³	2,66
Hold-up volume, outer circuit	dm ³	2,77
Port size F1/P1	mm	24,0
Port size F2/P2	mm	24,0
Port size F3/P3	mm	24,0
Port size F4/P4	mm	24,0
NND F1/P1	mm	27,0
NND F2/P2	mm	27,0
NND F3/P3	mm	27,0
NND F4/P4	mm	27,0
Carbon footprint	kg	77,3

РАЗМЕРЫ



A	mm	524 to 526 +/-2
B	mm	117 to 119 +/-1
C	mm	479 +/-1
D	mm	72 +/-1
E	mm	20 (opt. 45) +/-1
F	mm	114,50 to 120,50 +/-3%
G	mm	4 to 7 +/-1
R	mm	22 to 23

This is a schematic sketch. For correct drawings please use the order drawing function or contact your SWEP representative.

Disclaimer: Data used in this calculation is subject to change without notice. SWEP strives to use "best practice" for the calculations leading to the above results. Calculation is intended to show thermal and hydraulic performance, no consideration has been taken to mechanical strength of the product. Product restrictions - such as pressure, temperatures and corrosion resistance- can be found in SWEP product sheets and other technical documentation. SWEP may have patents, trademarks, copyrights or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from SWEP, the furnishing of this document does not give you any license to these patents, trademarks, copyrights, or other intellectual property. To the maximum extent permitted by applicable law, the software, the calculations and the results are provided without warranties of any kind, whether express or implied. No advice or information obtained through use of the software (including information provided in the results), will create any warranty not expressly stated in the applicable license terms. Without limiting the foregoing, SWEP does not warrant that the content (including the calculations and the results) is accurate, reliable or correct. SWEP does not warrant that any system comprising heat exchanger and other components, installed on the basis of calculations in this software, will meet your requirements or function to your satisfaction or expectations.

*Excluding pressure drop in connections.



PFH77GWGS4NXAQEO22FJZPAHLMAKWN4KKKW6IPA